

RANCH HAND

1-800-366-9712

INSTALLATION INSTRUCTIONS

PART # RHU001BLB

BOLT ON RECEIVER HITCH

RATED FOR WEIGHTS OF –500lbs. TONGUE / 5,000lbs. DRAW

1. Mount the bolt on receiver hitch onto the drop plate of the Ranch Hand bumper.
2. Use two 3/4" x 2" bolts and two 1/2" x 2" bolts to install.
3. **MAKE SURE ALL NUTS AND BOLTS ARE TIGHT!**

WARNING

Special care should be exercised in the handling, storage and installation of Kaspar Ranch Hand equipment. The actual weight of each piece of equipment will vary depending on style and model. The weight of the equipment is sufficient in volume to warrant special care, assistance and in some instances, the use of mechanical equipment during the transfer and installation of the equipment.

Do not assume a position directly under the equipment during installation. Be sure the equipment has been connected and stabilized during installation to prevent falling or shifting of positions.

Periodically check tightness of bolts to make sure they are tight, and unlikely to fail.

Rev. 1/14/09

RANCH HAND

1-800-366-9712

INSTALLATION INSTRUCTIONS

PART # RHU001BLB

BOLT ON RECEIVER HITCH

RATED FOR WEIGHTS OF –500lbs. TONGUE / 5,000lbs. DRAW

1. Mount the bolt on receiver hitch onto the drop plate of the Ranch Hand bumper.
2. Use two 3/4" x 2" bolts and two 1/2" x 2" bolts to install.
3. **MAKE SURE ALL NUTS AND BOLTS ARE TIGHT!**

WARNING

Special care should be exercised in the handling, storage and installation of Kaspar Ranch Hand equipment. The actual weight of each piece of equipment will vary depending on style and model. The weight of the equipment is sufficient in volume to warrant special care, assistance and in some instances, the use of mechanical equipment during the transfer and installation of the equipment.

Do not assume a position directly under the equipment during installation. Be sure the equipment has been connected and stabilized during installation to prevent falling or shifting of positions.

Periodically check tightness of bolts to make sure they are tight, and unlikely to fail.

Rev. 1/14/09